Description of Materials

U.S. Department of Housing and Urban Development **Department of Veterans Affairs Farmers Home Administrtation**

Public reporting burden for this collection of information is estimated to average 30 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. This agency may not collect this information, and you are not required to complete this form, unless it displays a currently valid OMB control number.

The National Housing Act (12 USC 1703) authorizes insuring financial institutions against default losses on single family mortgages. HUD must evaluate the acceptability and value of properties to be insured. The information collected here will be used to determine if proposed construction meets regulatory requirements and if the property is suitable for mortgage insurance. Response to this information collection is mandatory. No assurance of confidentiality is provided.

X Proposed Construction Under Construction	No	(To be inserted by HUD, VA or FmHA)
Property address (Include City and State)		

Name and address of Mortgagor or Sponsor	Name and address of Contractor or Builder	F
	CELEBRITY HOMES 14002 L STREET OMAHA, NE 68137	25 2000

Instructions

1. For additional information on how this form is to be submitted, number of copies, etc., see the instructions applicable to the HUD Application for Mortgage Insurance, VA Request for Determination of Reasonable Value, or FmHA Property Information and Appraisal Report, as the case may be. 2. Describe all materials and equipment to be used, whether or not shown on

the drawings, by marking an X in each appropriate check-box and entering the information called for each space. If space is inadequate, enter "See

misc." and describe under item 27 or on an attached sheet. The use of paint containing more than the percentage of lead by weight

3. Work not specifically described or shown will not be considered unless required, then the minimum acceptable will be assumed. Work exceeding minimum requirements cannot be considered unless specifically described.

4. Include no alternates, "or equal" phrases, or contradictory items. (Consideration of a request for acceptance of substitute materials or equipment is not thereby precluded.)

5. Include signatures required at the end of this form.

6. The construction shall be completed in compliance with the related drawings and specifications, as amended during processing. The specifications include this Description of Materials and the applicable Minimum Property Standards.

1. Excavation

permitted by law is prohibilited.

Bearing soil, type __SANDY CLAY, GOOD FOUNDATION SOIL

Foundations 2.

	Footings concrete mix <u>READY MIX</u> strength	n psi <u>2000 LBS</u> Reinforcing	2 - #4 STEEL REBAR
	Foundation wall material8" POURED CONC	Reinforcing	STEEL REBARS
	Interior foundation wall material8" POURED CONC	Party foundation wall _8" POURED	CONC
	Columns material and sizes STEELPIPE		
	Girders material and sizes STEEL	Sills material WOOD, TREATED	
	Basement entrance areaway _POURED CONCRETE	Window areaways GALVANIZED S	
	WaterproofingWATERPROOF SPRAY ON POURED FOUND	Footing drainsPERFORATED P	
	Termite protection _SOIL TREATMENT BY BONDED EXTERMINA	TOR	
	Basementless space ground cover insu	lation fou	indation vents
	Special foundations		
	Additional information		с. С
3.	Chimneys		
	Material GAS HEAT MTL TYPE B Prefabricated (m	nake and size)	
	Flue lining material Heater flue size	5" MTL TYPE B Firepla	ace flue size
	Vents (material and size) gas or oil heater 4" 26 GAUGE GALV. O	R 2"-3" PVC water heater	3" 26 GAUGE GALV.
	Additional information		
4.	Fireplaces		14 E
	Type solid fuel x gas-burning circulator (make and size	9)	Ash dump and clean-out
		hearth	
	Additional information		
	£ 4.		
	The Control of Control		

5.	Exterior Walls								
	Wood frame wood grade, and species _	SPI	F CONS 2X4	/1600		Corner b	racing Building pap	per or felt	
	Sheathing FOAM SHEATHNG	thickness	<u>1/2"</u>	width <u>48"</u>	X	solid	spaced	o.c. 🔄 diagonal	
	Siding HARDBOARD	grade P	RIMED	type PLA	N size	SOLID	exposure SOLI	D fastening NAILED	<u> </u>
	Shingles	grade		type	size)	exposure	fastening	
	Stucco	thickness	;	Lath				weight	_ lb.
	Masonry veneer		Sills		Linte	ls	Base	flashing	<u> </u>
	Masonry solid faced	stuccoed t	otal wall thick	ness	. <u> </u>	facing thic	kness	facing material	
۰.	Backup materialthick	iess	boi	nding			-		
	Door sills WOOD	Windo	w sills WOO	D		Lintels	Bas	e flashing	
	Interior surfaces dampproofing,	_ coats of _				fu rri n	9	·	
	Additional information								
	Exterior painting material 100% ACRY	LIC LATE	X					number of coats _1	
	Gable wall construction X same as n								
6.	Floor Framing	l							
	Joists wood, grade, and species								
	Concrete slab X basement floor] first floor	r 🗙 groun	d supported	d 🗌 sel	lf-supporting i	mix 2500#	thickness <u>3 1/2"</u>	
	reinforcing								
	Fill under slab material		thic	kness					
	Additional information PRE-ENG FLC	OR TRUS	SSES						
7.	Subflooring (Describe underflooring			er item 21)					
••	Material grade and species 5/8" OSB	•		•		ИNT	_{size} 4'X8'	type TONG & GRVE	
	Laid X first floor X second floor					al X right			
	Additional information				*		0		
8.	Finish Flooring (Wood only. Describe	other fini	sh flooring u	nder item	21)				
	Location Rooms	Grade	Species	Thickness	6 Width	Bidg. Pape	7	Finish	
	First floor				-				
	Second floor Attic floor sq. ft.			_					
	Additional information	-		_	ļ				
9.	Partition Framing								
	Studs wood, grade, and species PRE-	ENG. WAL	LS	_ size an	d spacing 2	2X4 - 240C	(Other	
	Additional information								
10	Ceiling Framing	.LS@10	0.0.						
	Joists wood, grade, and species PRE-I	ENG. TRU	JSS	Other	2X6 - 24	oc	Bridaina		
	Additional information								
11.	Roof Framing					n /n n n nhai-200		_	
	Rafters wood, grade, and species Roof trusses (see detail) grade and species								
	Additional information PRE-ENG TRU	SS @ 24"	0.C.			·			
12.	Roofing						_		
	Sheathing wood, grade, and species 7/16" OSB WITH PLYCLIPS						X so		0.C.
	Roofing FIBERGLASS grade 25 YEAR						SELF-SEALING		
	Underlay ASPHALTIC FELT							fastening	
	Built-up roofing							aterial	
	Flashing material GALVANIZED MET.	AL			gage or w	eight 26 GA	<u> </u>	gravel stops 📃 snow gua	ards
	Additional information								

13.	Gutters and Downs						
	Gutters material <u>GA</u>	ALV. METAL	gage or weight26	size <u>5</u> "	shape <u>K</u> ST	YLE	
	Downspouts material	GALV. METAL	gage or weight 26	size_3	shape	RECT number	
	Downspouts connect	ted to Storm sewer	sanitary sewer drv-well	X Splash bloc		d size FLIP-UPS	
	Additional information						
14.	Lath and Plaster		r				
	Lath walls	ceilings material	weight or thickness	Plaste	r coats	finish	
		X ceilings material DRYW				finish_TEXTURED	
		L					
		PE,FLOAT,SAND & TEXTU	RE				
15.	Decorating (Paint, v	vallpaper, etc.)					
	Rooms		erial and Application			terial and Application	
-	litchen	DRYWALL, TEXTURE, PAIN		DRYWALL, T			
	lath Dther	DRYWALL, TEXTURE, PAIN		DRYWALL, 1	EXTURED	<u></u>	
<u>~</u>							
A	dditional information	FLAT LATEX INTERIOR PA	AINT				
16.	Interior Doors and 1						
		W CORE 6 PANEL OR 2 PA					
	Door trim type PRE	FINISHED material					
	Finish doors FACT	ORY -FINISHED	trim _	PRE-FINISHED			
	Other trim (item, type	e and location) TRIM AND DC	DORS ARE PREFINISHED				
	Additional information	n . ·					
17	Windows						
		SLIDING make	VINYI met	ariat VINYL		_ sash thickness	
	Glass grade <u>THER</u>					head flashing	
						number coats	
						Storm sash, number <u>ALL</u>	
		half type					
			material VINYL	screens, numbe	er <u>ALL</u>	Storm sash, numberALL	
	Special windows SE	EPLANS					
	Additional information	n					
18.	Entrances and Exter	rior Detail					
	Main entrance door	material FGLS-GLS INS.	width 36" thick	ness 1.75 Fra	me material V	VOOD thickness 5	
		material VNYL PATIO DO	······	-			
	Head flashing AS REQUIRED Weatherstripping type PILE saddles Screen doors thickness number 1 screen cloth material FBRGLASS Storm doors thickness number 1						
		fixed Railings ALU					
	-					number coats	
	Additional information	ⁿ SEE EXTERIOR ELEVATI	IONS/ OTHER ENTRANCE	DOORS FGLS. I	NS. OR STEI	EL INS.	
19.	Cabinets and Interio	or Detail					
	Kitchen cabinets, wal	Il units material OAK/BIRCH	PANEL	lineal	feet of shelve	s PLN shelf width 12"	
	Base units mate	rial OAK/BIRCH PANEL	counter top LAM	NATED PLAST.	edgi	ng LAMINATED PLAST.	
						number coats	
		uilt-in furniture BATH VANIT					
	Auditional Information	MIRROR @ VANITIES					

_

-

·____

20. Stairs

	Tre	ads	Ri	sers	Str	ings	Har	ndrail	Balus	ters
Stair	Material	Thickness	Material	Thickness	Material	Size	Material	Size	Material	Size
Basement	OSB	11/8"	OSB	5/8"	OSB	1 1/8X12	FIR	1 1/2"	IRON	
Main	OSB	11/8"	OSB	5/8"	OSB	1 1/8X12	OAK	1 1/2"	IRON	
Attic										

Disappearing make and model number _

Additional information

21. Special Floors and Wainscot (Describe Carpet as listed in Certified Products Directory)

	Location	Material, Color, Border, Sizes, Gage, Etc.	Threshold Material	Wall Base Material	Underfloor Material
ors	Kitchen	VINYL SHEET GOODS	ALUM	WOOD	PLYWOOD
Ĕ	Bath	VINYL SHEET GOODS	ALUM	WOOD	PLYWOOD
	· · · · · · · · · · · · · · · · · · ·				·
g	Location	Material, Color, Border, Cap. Sizes, Gage, Etc.	Height	Height Over Tub	Height in Showers (From Floor)
ains	Bath	FIBERGLASS TUB/SHOWER ENCLOSED			
Ň	3/4 BATH	FIBERGLASS SHOWER ENCLOSED			

Additional information

22. Plumbing

Flumbing			·					
Fixture	Number	Location	Make	MFR's Fixture Id	entification No.	Size	Color	
Sink	1	KITCHEN	ELKEY			33X22	S.S.	
Lavatory	5	BATH	PORCELAIN DROP-IN				WHITE	
Water closet	3	BATH	MANSFIELD				WHITE	
Bathtub			· · · · · · · · · · · · · · · · · · ·					
Shower over tub	1	BATH	MAAX			60"	WHITE	
Stall shower	1	BATH	MAAX			60"	WHITE	
Laundry trays								
ICEMAKER	1	KITCHEN	R.I. ONLY					
FAUCETS	5	LAVS	DELTA				CHROME	
Water supply X pu Sewage disposal X House drain (inside) Water piping ga	3/4 B/ Door Iblic public cast Ivanized r type <u>N/</u>	Shower pa	x other PLASTIC	HOWER ST * (Show draw e) system* ivate) system* House sewer (ou C	v and describe individ lings and specificatio tside) cast irro heating capaci	ual system in comple ns according to requi on tile Sill cocks, num	ete detail in separate rements.) other <u>PLASTIC</u> ber 2	
Gas service X utilit	v compa	nv 🗌 lia. pet.	gas other		Gas piping	cooking	X house heating	
Footing drains connected to storm sewer sanitary sewer dry well X Sump pump make and model <u>HYDROMATIC AS REQD</u>								
capacity			discharges into OPE	NAIR AS REQUIRE	<u>.D</u>			
Additional information	1							

23.	Heating
	Hot water Steam Vapor One-pipe system Two-pipe system
	Radiators Convectors Baseboard radiation Make and model
	Radiant panel floor wall ceiling Panel coil material
	Circulator Return pumpMake and model gpm.
	Boiler make and model Btuh. net rating Btuh.
	Additional information
	Warm air Gravity X Forced Type of system GAS
	Duct material supply GALV. MTL Insulation thickness Outside air intake Furnace: make and model LENNOX 90% EFF Input 88,000 Btuh. output 82,000 Btuh.
	Additional information
	Space heater floor furnace wall heaterInput Btuh. output Btuh. number units
	Make, model
	Additional information
	Controls make and types HONEYWELL FOCUS PRO 5000
	Additional information
	Fuel: Coal oil X gas liq. pet. gas electric other storage capacity
	Additional information
	Firing equipment furnished separately Gas burner, conversion type Stoker hopper feed bin feed
	Oil burner pressure atomizing vaporizing
	Make and model
	Control
	Additional information
	Electric heating system type Input watts @ volts output Btuh.
	Additional information
	Ventilating equipment attic fan, make and model capacity cfm.
	x kitchen exhaust fan, make and model INCLUDED WITH MICROWAVE
	Other heating, ventilating, or cooling equipment LENNOX A/C 3 1/2 TON
	TEXTAUST FAN EACH BATH
24.	Electric Wiring Service Overhead X underground Panel fuse box X circuit-breaker make CHALLENGER AMP's 125 No. circuits
	X Doorbell X Chimes Push-button locations
	Additional information PREWIRE TELEPHONE/CABLE JACKS
25	
	ighting Fixtures Total number of fixtures SEE PLAN Total allowance for fixtures, typical installation, \$
	Nontypical installation _ALL FIXTURES PROVIDED BY CONTRACTOR INCLUDING 2 CEILING FANS
÷	

.

_

26.	Insulation

Location	Thickness	Material, Type, and Method of Installation	Vapor Barrier
Roof			
Ceiling		R-50 BLOWN IN FLAT, R-38 @ SLOPES	POLYSLOPE
Vall	3 1/2"	R-15 FBRGLASS BATT	POLY-FILM
loor	6"	R-30 FBRGLASS BATT, UNHEATED AREA	
		1/2" UNSUL SHEATH, EXT WALLS	

27. Miscellaneous: (Describe any main dwelling materials, equipment, or construction items not shown elsewhere; or use to provide additional information where the space provided was inadequate. Always reference by item number to correspond to numbering used on this form.)

HBW 2-10 WARRANTY, SLOPED CEILINGS PER PLAN, CARPET - \$15.00/YD & UPGRADE PAD (STD ALLOWD), WINDOW BLINDS

Hardware (make, material, and finish.)

KWIKSET, BRUSHED NICKEL

Special Equipment (State material or make, model and quantity. Include only equipment and appliances which are acceptable by local law, custom and applicable FHA standards. Do not include items which, by established custom, are supplied by occupant and removed when he vacates premises or chattles prohibited by law from becoming realty.)

1-GE S.C. ELEC RANGE,1- GE MICRO OTR,1-GE DISH,1-BADGER GARBGE DISPOSAL,1-GE REF,1-GE WASH,1-GE DRY,

Porches

3 1/2" THICK CONCRETE FRONT STOOP SLAB, 15'x12' PATIO ON BACK

Terraces

Garages

3- CAR GARAGE WITH 3 1/2" CONCRETE FLOOR, 16X7 & 9X7 STEEL INSULATED RSD PNL GARAGE DOOR, PREWIRE FOR OPENER

Walks and Driveways

Driveway width 26'-8"	base material DIRT	thickness	surfacing material	POURED CNCRTE	thickness 3.5"
Front walk width 36"	material CONCRETE	thickness 3.5"	Service walk width 24"	material <u>CONCR</u>	thickness 3.5"
Steps material	CONCRETE	treads 10" rise	s 7 3/4" Cheek walls		

Other Onsite Improvements

(Specify all exterior onsite improvements not described elsewhere, including items such as unusual grading, drainage structures, retaining walls, fence, railings, and accessory structures.)

AS PER PLAN

Landscaping, Planting, and Finish Grading				
Topsoil <u>2</u> " thick X front yard X side yards	X rear yard	to <u>ALL</u> feet	t behind main building	
Lawns (seeded, sodded, or sprigged) X front yard	SEEDED	X side yards <u>SEEDED</u>	X rear yard	SEEDED
Planting as specified and shown on drawings	as follows:			
<u>1</u> Shade trees deciduous <u>1 1/2</u> caliper		Evergreen trees	to	B & B
Low flowering trees deciduous	to	Evergreen shrubs	to	B&B
High-growing shrubs deciduous	_ to	Vines, 2-year		
Medium-growing shrubs deciduous	_ to	Other		
Low-growing shrubs deciduous	_ to			
Identification—This exhibit shall be identified by the signa	ture of the builde	er, or sponsor, and/or the pronoser	mortgagor if the latter	is known at the time
of application.		···; -·; -····; -···· ··· ··· ···		io known at tho time

Date (mm/dd/yyyy)_

Signature

Signature